

	K9-4	K9-3
Engine		
Make	Yanmar (Diesel) Kohler (Petrol)	Perkins (Diesel) Kohler (Petrol)
Power	27HP / 20.1kW 25HP / 18.6 kw	20HP / 15kW 22HP / 16.4 kw
Performance		
Hydraulic Pumps	2 pumps	2 pumps
Pump Sizes	11 & 4 cc 9 & 4 cc	11 & 3 cc 9 & 3 cc
Hydraulic Relief Pressure	235 bar (3400psi)	206 bar (3000psi)
Hydraulic Pump Output	47 l/min	43 l/min
Travel Speed (with overdrive)	0-7.4 km/h	0-7.4 km/h
Rate Lift Capacity	SWL: 325 kg MWL: 650 kg	SWL: 250 kg MWL: 500 kg
Wheel Motors	4 x 29 cu in	2 x 29 cu in
Auxiliary Hydraulic Outlets	4	1
Dimensions		
A. Overall Width	970mm	1050mm
B. Overall Length	1550mm	1565mm
C. Overall Height	1200mm	1200mm
D. Maximum Operating Height with 4 in 1 Bucket	2650mm	2080mm
E. Turning Radius with 4 in 1 Bucket	1300mm	1300mm
F. Angle of Departure	25°	20°
G. Wheel Base	800mm	710 - 800 mm
H. Ground Clearance	135mm	135mm
I. Dump Height Std Bucket	1450mm	1240mm
J. Reach Fully Raised Std Bucket	800mm	600mm
K. Dump Height with 4 in 1 Bucket	1835mm	1750mm
L. Reach Fully Raised 4 in 1 Bucket	800mm	600mm
M. Height to Hinge Pin	1940mm	1680mm
N. Machine width with 4 in 1 Bucket	1050mm	1050mm
Hydraulic Reservoir	90 L	60L
Machine Mass	Yanmar 925kg Kohler 840kg	745kg approx
Security Immobiliser	Standard	Standard
Warranty		
Engine Warranty	2 Years *	2 Years *
Product Warranty	2 Years / 1000hrs *	2 Years / 1000hrs *